

# RUSH+ SMALL

The RUSH+ SMALL adopts all the features of the popular Rush+ model just in a smaller fit. An ultra-sporty design with its co-injected and ultra-flexible temples.



1672301 : Clear Lens



1672302 : Smoke Lens



1672301PW : Clear Lens



1672302PW : Smoke Lens



Adjustable PVC nose bridge.

 **PLATINUM**















26 g


- + BUILT IN BROW PROTECTION**
- +  PLATINUM COATING (  )**
- + ULTRA LIGHT WEIGHT, 9 BASE**
- + ADJUSTABLE PVC NOSE BRIDGE**
- + CO-MOULDED TEMPLE ARMS FOR COMFORT & GRIP**

**bolle**  
SAFETY

# RUSH+ SMALL

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
<b>RUSH+ SMALL</b>	 Clear / Blue	1672301	IO & 	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/Platinum 
	 Smoke / Blue	1672302	I3 & 	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/Platinum 
	 Clear / Pink	1672301PW	IO & 	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/Platinum 
	 Smoke / Pink	1672302PW	I3 & 	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/Platinum 

## LENS MARKING

 Platinum is a permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd / m<sup>2</sup>), to the most aggressive chemicals and delays the onset of fogging for 2 minutes, as per the testing requirements of EN166.

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

## OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear).
- 3. Range of luminous transmittance 8 -18% (smoke).

## APPLICATIONS

- Assembly and production work
- Process work
- Emergency response
- Driving
- Solar UV exposure
- Laboratory


## MAIN MARKETS

- Manufacturing
- Petrochemical
- Construction
- Government
- Mining
- Medical and dental
- Food industry

## LENSES

- 2mm polycarbonate
- 9 base curve
- Platinum coating on both side of clear and smoke lenses
- 99.9% UV 385 – Clear
- 99.9% UV 400 – Smoke

## CLEANING AND STORAGE

**CLEANING :** Bollé Safety recommends only using our  BOLLÉ CLEAN Lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** Store between 5 and 40 °, humidity <90%.

## CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 9
FRAME	PC
TEMPLES	PC + TPR
STRAP	Non Applicable
FOAM	Non Applicable
SPARE LENSES	No

## FRAME MARKING

**AS/NZS 1337.1.2010 :** Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

**ASIA/PACIFIC HEADQUARTERS :**  
Bollé Safety AU Pty Limited  
32-40 Fairchild Street  
Heatherton VIC 3202  
T: 1300 138 098  
E: safety@bolle.com.au

**NEW ZEALAND:**  
T.: 0800 2655 369  
E: bolle@bolle.co.nz

[bollesafety.com.au](http://bollesafety.com.au)

**bolle**  
SAFETY