

SHOWA

731

Created with premium-grade plasticizers and 100% nitrile with Eco Best Technology, this glove brings you the pinnacle of tactile precision and high-capacity protection against solvents and acids.

[FEATURES

- 100% Biodegradable nitrile with Eco Best Technology® (EBT)
- Chemical protection against solvents and acids
- Bisque finish grip makes wet work easier and safer
- Tactile precision
- Unsupported, flock-lined
- 15 mil thick, 13" long
- 21 CFR 177.2600 / FDA compliant for direct food contact

[BENEFITS

SHOWA's gloves with Eco Best Technology (EBT) are engineered for accelerated biodegradation in biologically active landfills. Independent certified laboratories performing long-term landfill biodegradation testing according to ASTM D5526-12 reported that Showa's gloves with EBT achieved 82.0% biodegradation in only 386 days, while gloves without EBT achieved only 1.9% biodegradation over the same period of time. These results may not be indicative of future biodegradation.

[INDUSTRY



Aerospace



Agriculture



Automotive



Chemical



Engineering



Food



Janitorial



Landscaping



Municipal Services



Oil and Gas

[IDEAL APPLICATIONS

- Chemical spray and treatment
- Handling plants and vegetables
- Light chemical handling in agriculture, horticulture
- Light assembly of oil-coated pieces
- Coating preparation
- Assembly dry and oily parts
- Food packing and handling
- Washing & cleaning
- Handling plants and vegetable
- Deck crew



TAA PRODUCTS

MATERIAL

- Cotton flock
- Unsupported

COATING

- Biodegradable
- chemical resistant
- Nitrile
- Water resistant

GRIP

- Bisque

STANDARDS



2777

EN ISO 374-1:2016/Type A



JKLOPT

EN 388:2016



2001X

EN ISO 374-5:2016



SHOWA
731



PACKAGING

- 12 Pair per polybag
- 12 Polybags per case
- 144 Pair per case



COLOUR

- Green



SIZES

- XS
- S
- M
- L
- XL
- XXL



THICKNESS

- 15 mil



[YOU MIGHT ALSO BE INTERESTED IN

SHOWA
707HVO



MATERIAL
Unsupported

COATING
Biodegradable

SHOWA
6110PF



MATERIAL
Single use

COATING
Biodegradable

SHOWA
CHM



MATERIAL
Cotton flock

COATING
chemical resistant

SHOWA
772



MATERIAL
Cotton

COATING
chemical resistant

[USER INSTRUCTIONS

Protection against mechanical risks, with electrostatic properties. Do not use where there are electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light. All clothing and shoes worn with the glove with electrostatic dissipation properties must also be designed taking the electrostatic risk into account.

[DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Get in touch

SHOWA USA | 579 Edison Street - Menlo, GA 30731, USA

USA@SHOWAGroup.com

© SHOWA Group 2018 | All rights reserved