





SHOWA

NSK24

Blue

Providing excellent protection from a wide array of solvents, oils and acids, this glove is super flexible, watertight, knit-lined nitrile glove that is engineered with SHOWA's biodegradable Eco Best Technology (EBT) technology.

FEATURES

- 100% Biodegradable nitrile coated with cotton interlock liner
- Double nitrile coating provides excellent chemical, oil and abrasion resistance
- Nitrile protects the hand from oils, hydrocarbons and grease penetration
- Cotton liner absorbs perspiration and adds comfort
- The rough textured finish ensures excellent grip
- No natural rubber allergy risks
- 14" long
- Rough grip
- 21 CFR 177.2600 / FDA compliant for direct food contact

BENEFITS

SHOWA's gloves with Eco Best Technology (EBT) are engineered for accelerated biodegradation in biologically active landfills. Independent certified laboratories performing long-term landfill biodegradation testing according to ASTM D5526-12 reported that Showa's gloves with EBT achieved 82.0% biodegradation in only 386 days, while gloves without EBT achieved only 1.9% biodegradation over the same period of time. These results may not be indicative of future biodegradation.

INDUSTRY



Agriculture



Automotive



Chemical



Food



Janitorial



Oil and Gas



Utilities

IDEAL APPLICATIONS

- Light chemical handling in agriculture, horticulture
- Painting and spray workshops
- Chemical spray and treatment
- Coating preparation
- Painting & spray workshops
- Food Service/Food Prep
- Sanitation and dishwashing
- Washing & cleaning
- Deck crew
- Water/Sewage treatment



TAA PRODUCTS

MATERIAL

- Cotton
- Cut and sewn

COATING

- Biodegradable
- chemical resistant
- Nitrile
- Water resistant

GRIP

Rough

STANDARDS





EN ISO

FN 388:2016









NSK24

Blue



PACKAGING

- 12 Pair per polybag
- 6 Polybags per case
- 72 Pair per case



COLOUR

Royal blue





- _____ M
 - XL



YOU MIGHT ALSO BE INTERESTED IN





Cotton
COATING
chemical

resistant

707HVO



MATERIAL
Unsupported
COATING
Biodegradable

SHOWA CHM



MATERIAL Coton flock COATING chemical resistant SHOWA N8



MATERIAL Unsupported COATING Neoprene

USER INSTRUCTIONS

Protection against mechanical risks, with electrostatic properties. Do not use where there are electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light. All clothing and shoes worn with the glove with electrostatic dissipation properties must also be designed taking the electrostatic risk into account.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.



